


MIL-55310/19-Series Specifications



0.480L x 0.480W x 0.085H (in)

PDI MIL-PRF-55310/19 Oscillators are available in both standard and custom frequencies to provide precision timing in a hermetically sealed package for military and avionics applications.

ex) **M55310/19—B—12—A—25M00000**

MILITARY SLASH SHEET

PRODUCT LEVEL

B = Hi-Rel
C = Commercial

DASH NUMBER

See Chart Below

OPERATING TEMPERATURE

A = -55 to +125°C
B = -55 to +105°C
C = -20 to +70°C

XXXXXXXX

Specified
Nominal
Frequency

Dash No.	Frequency Range	Input Current (1) Max	Rise/Fall Times Max	Duty Cycle @ 1.4 Vdc	Load (2) Max	Initial Accuracy @ 23°C ppm Max	Aging Per Year ppm Max	Operating Temperature		
								(A)	(B)	(C)
01	1 MHz to 16 MHz	75 mA	15 nS	40 to 60%	10 TTL	±25	±10	±100	±75	±50
02						±25	±10	±200	±150	±100
03						±15	±5	±50	±40	±25
11	16 MHz to 40 MHz	40 mA	5 nS	40 to 60%	10 TTL	±25	±10	±100	±75	±50
12						±25	±10	±200	±150	±100
13						±15	±5	±50	±40	±25
21	40 MHz to 60 MHz	70 mA	5 nS	40 to 60%	10 TTL	±25	±10	±100	±75	±50
22						±25	±10	±200	±150	±100
23						±15	±5	±50	±40	±25
Aging Per Year (Max) (Measurements shall be taken @+70°C ±0.2°C at intervals of not more than every 72 hours for 30 days minimum)							±5 ppm		±10 ppm	
Per 30 Days							±0.7 ppm		±1.5 ppm	
Per 90 Days							±1.5 ppm		±3.0 ppm	
NOTES:										
(1) Maximum input current for no load condition. Actual configuration of TTL loads must be added to determine power supply requirements.										
(2) A TTL unit load is defined as: 1.60 mA sink, 0.04 mA source, and 2.0 pF capacitance.										

Environmental Specifications

Terminal Strength	MIL-STD-202 , Method 211 , Condition C Applied Force: 2 pounds each terminal for 10 seconds , Bends: 5 at 45 degrees each
Vibration, sinusoidal	IAW MIL-PRF-55310 and MIL-STD-202 , Method 204 Non-operating: Test Condition D, Operating: Not Required
Ambient Pressure	Non-operating: IAW MIL-PRF-55310 , Operating: MIL-STD-202 , Method 105 , Condition C
Reflow Soldering	Reflow soldering of the unit @ +230°C ±10°C for 15 seconds shall not degrade the performance.

The product described in this spec. consist of this specification and MIL-PRF-55310.

Decimal XXX = ± .005, XX = ± .020 Metric [XXX = ± .13], [XX = ± .50]

REV: NA

SIZE: A

CAGE: A

1 of 3

Parameter		Frequency Range	Units
		1MHz to 60MHz	
Frequency Stability	vs Temperature (Max)		ppm
	-20 to +70°C (Type C)	Per Chart	
	-55 to +105°C (Type B)	Per Chart	
	-55 to +125°C (Type A)	Per Chart	
	vs Supply Voltage (Max. for a 10% change) (Measurements taken at reference temperature and operating temperature range end points)	±4.0	
	Tolerance (@ +23°C ± 1.0°C) (Max) Within 30 Days of Shipment	Per Chart	
Temperature Range	Operating	Per Chart	°C
	Storage	-62 to +125	
Supply Voltage	±10.0 %	+5.0	Vdc
Output		TTL	
Logic Levels	High (Min) @ 400 µA Source	2.4	Vdc
	Low (Max) with 16 mA Sink	0.5	

Test Inspection	Product Level B Method Condition
Internal Visual	MIL-STD-883, Method 2017 and 2032
Stabization bake (prior to seal) 1/	MIL-STD-883, Method 1011, Condition C (+150°C) 48 hours min.
Temperature Cycling	MIL-STD-883, Method 1010 Condition B
Constant Acceleration	MIL-STD-883, Method 2001. Condition A, Y1 only (5000 g's)
Seal (Fine and Gross Leak) 2/	MIL-STD-883, Method 1014
Burn-In (Load)	+125C, nominal supply voltage and burn-in load, 160 hours minimum
Electrical Test:	Nominal supply voltages, specified load, +23°C and verify frequency at the temperature extremes
Input Current Power	4.8.5 of MIL-PRF-55310
Output Waveform	4.8.20 of MIL-PRF-55310
Output Voltage-Power	4.8.21 of MIL-PRF-55310
As Specified	3.1 of MIL-PRF-55310

MIL-55310/19-Series 0.480 x 0.480 x 0.085 (in)

PACKAGE DIMENSIONS

PIN	CONNECTION
1-3	No Connect
4	Supply Voltage
5-9	No Connect
10	Supply Voltage
11-30	No Connect
31	Ground
32-36	No Connect
37	Ground
38	No Connect
39	Output
40	No Connect

